

## **Chain Couplings**


Chain couplings are composed of a duplex roller chain and a pair of coupling sprockets. The function of the connection and detachment is done by the joint of the chain. It has the characteristic of compact and powerful, excellent durability, safe and smart, simple installation and easy alignment. Our chain couplings are suitable for a wide range of coupling applications.











| Chain<br>Coupling No. | Bore Dia  |           | Dimensions |         |         |         |         |         | Torque<br>Rating | Complete<br>Weight |
|-----------------------|-----------|-----------|------------|---------|---------|---------|---------|---------|------------------|--------------------|
|                       | MIN<br>mm | MAX<br>mm | A<br>MM    | B<br>MM | C<br>MM | D<br>MM | E<br>MM | F<br>MM | Nm               | KG                 |
| 4016                  | 14        | 30        | 92         | 75      | 80      | 36      | 50      | 77      | 380              | 1.8                |
| 5016                  | 16        | 40        | 111        | 85      | 100     | 45      | 60      | 92      | 725              | 3.2                |
| 5018                  | 16        | 45        | 123        | 85      | 100     | 45      | 70      | 106     | 925              | 4.0                |
| 6020                  | 20        | 70        | 160        | 108     | 123     | 54      | 98      | 132     | 2050             | 9.5                |
| 8020                  | 30        | 85        | 211        | 138     | 144     | 67      | 120     | 184     | 4700             | 18.2               |